



**Electric system**

Input voltage	220 - 240 V	110 - 120 V
Frequency	50/60 Hz	50/60 Hz
Nominal power	1100 W	1000 W
Electric current	5A	9A
Type of motor	Universal with Preheat*	Universal with Preheat*
Motor speed	23000 RPM	21500 RPM
Working temperature	40 °C/104 °F	40 °C/104 °F

\*Patented by ffuuss™

**Manufacturing**

Cover material: ABS
Treated with Biomaster Silver Ions antibacterial additive
Finish: Various colours
Mounting mooring: Galvanized steel
Water inlet protection: IPX2
Filter: HEPA H13

**Operation**

Automatic activation
Approx hand drying time: 12 seconds
Blocking time: 25 seconds
Airflow: Up to 73 l/s (19,3 gal/s)

**Logistics**

Net weight: 7,7 Kg (16,1 lb)
Gross weight: 9,2 Kg (19,4 lb)
Box dimensions: 690mm / 360mm / 285mm (H27 1/64" W14 1/64" D11 7/32")

**Regulations**

This device complies with the following directives/normatives:  
1999/5/CE 2004/108/CE 2006/95/CE  
2002/96/EC 2011/65/EC



**Others**

This unit has Bluetooth™ technology

**Standard warranty**

5 years for parts and 1 year for labour (see conditions)

**NOTE:** ffuuss™ reserves the right to make changes without prior notice.